



# Vigilant<sup>®</sup> LED High Bay & Low Bay

## Technical Specification Sheet - CE



FEBRUARY 2025

# Vigilant® LED High Bay - CE

## Corded Model & Integrated Wiring Box Model



### Corded Model



#### Mechanical Information:

**Fixture weight:**  
8.2 kg (18 lbs)

**Shipping weight:**  
10.9 kg (24 lbs)

**Mounting:**  
Stainless Steel Hook

**Power Cord:**  
3 meters, H07RN-F or H07BN4-F Heavy Duty

**Prefix:** HEE

#### Certifications & Ratings:

EN 60598-1:2015, IEC 60598-1:2014 (Polycarbonate lens)  
EN 60598-2-1:1989, IEC 60598-2-1:2020 IK06 to EN 50102 (Acrylic lens)  
IEC60068 IK05 to EN 50102 (Glass lens)  
Salt spray testing - severity 1 D-Marking to EN 60598 2-24  
IP66 to EN 60529 ENEC  
IK10 to EN 50102 L70 >150,000 hours @ 25°C ambient

#### Variable Dimming as Standard:

**Variable Dimming Control:** 0-10 VDC

**Dimming Range:** 10 VDC = 100% light output  
0 VDC = <10% light output

#### Electrical Specifications:

**Operating Voltage:** 100-277 VAC  
120-250 VDC

**Total system power consumption:** See table

**Operating Temp:** -40°C to +65°C

**Harmonics:** IEC 61000-3-2

**Noise requirement /EMC:** EN 61547: 2009  
Radiated and Conducted Emissions: EN 55015

**EMC Immunity:** EN 61547: 2009

**Transient protection:** 100-277 VAC models tested to withstand up to 8kV/4kA per IEEE C62.41.  
347-480 VAC models tested to withstand up to 6kV/3kA per IEEE C62.41

**THD:** < 20%

**Power Factor:** > 0.9

#### Power Supply:

**ALT: (accelerated life testing)** Over 15 yr equivalent at 24/7 service

**MTBF: (mean time between failures)** Over 300 years with annual failure rate less than 0.3% expected

**Driver:** Fully potted and sealed for superior protection

#### Construction:

**Housing:** Copper-free aluminium

**Finish:** Superior dual coat finish  
-Sealed polyester topcoat  
-Chemical-resistant epoxy primer

**Lens:** See table

**Screws:** Stainless steel 316

**Vibration:** Up to 5G @ 10-150Hz for 750,000 cycles, per IEC 60068-2-6 for luminaire only

**Shock:** 50G half-sine for 3 cycles, per IEC 60068-2-27 for luminaire only

#### Photometric Information:

**CRI:** 80

**CCT:** 5000K (cool white)  
4000K (neutral white)

All values typical unless otherwise stated (tolerance +/- 10%)

### Integrated Wiring Box



#### Mechanical Information:

**Fixture weight:**  
9.1 kg (20 lbs)

**Shipping weight:**  
11.8 kg (26 lbs)

**Mounting:**  
Various Kits (see page 15)

**Wiring Box Cable Entries:**  
M25 x 3

**Terminals:**  
0.5-4mm<sup>2</sup> x 5

**Prefix:** HWE

#### Comparison

	Warranty	L70
Dialight LED High Bay	10yr	>150,000
Metal Halide	1	15,000
High Pressure Sodium	1	20,000

**WARNING: INSTALLATION & SECONDARY RETENTION: The use of this product without proper installation and inspections, including secondary safety retention/securing, could cause severe injury or death. Dialight recommends that all installations should use secondary retention (appropriate to the installation environment) where applicable. It is the exclusive responsibility of the contractor, installer and/or end customer to: (a) determine the suitability of the product for its intended application; and, (b) ensure that the product is installed safely (with secondary retention where appropriate) and in compliance with all applicable laws and regulations. To the extent permissible under the relevant law, Dialight disclaims all responsibility for personal injury and/or other damage resulting from any dislodgement or other dislocation of this product.**

# Vigilant® LED High Bay - CE

## Battery Backup Model



### Mechanical Information:

**Fixture weight:**

17.7 kg (39 lbs)



**Shipping weight:**

20.9 kg (46 lbs)

**Mounting:**

Stainless Steel Hook

**Prefix:** HEE



Dimensions in mm (inches)

### Certifications & Ratings:

10 year warranty (excluding battery)	IK10 to EN 50102 (Polycarbonate lens)
EN 60598-1:2015,	IK06 to EN 50102 (Acrylic lens)
IEC 60598-1:2014	IK05 to EN 50102 (Glass lens)
EN 60598-2-1:1989,	D-Marking to EN 60598 2-24
IEC 60598-2-1:2020	L70 >150,000 hours @ 25°C ambient
IEC60068	
Salt spray testing - severity 1	
IP66 to EN 60529	

### Variable Dimming as Standard:

**Variable Dimming Control:** 0-10 VDC

**Dimming Range:** 10 VDC = 100% light output  
0 VDC = <10% light output

### Electrical Specifications:

<b>Operating Voltage:</b>	230/240 VAC
<b>Total system power consumption:</b>	See table
<b>Operating Temp:</b>	-20°C to +55°C
<b>Harmonics:</b>	IEC 61000-3-2
<b>Noise requirement /EMC:</b>	EN 61547: 2009 Radiated and Conducted Emissions: EN 55015
<b>EMC Immunity:</b>	EN 61547: 2009
<b>Transient protection:</b>	120-277 VAC models tested to withstand up to 6kV/3kA per IEEEE C62.41.
<b>THD:</b>	< 20%
<b>Power Factor:</b>	> 0.9
<b>Construction:</b>	
<b>Housing:</b>	Copper-free aluminium
<b>Finish:</b>	Superior dual coat finish -Sealed polyester topcoat -Chemical-resistant epoxy primer
<b>Lens:</b>	See table
<b>Screws:</b>	Stainless steel 316
<b>Photometric Information:</b>	
<b>CRI:</b>	80
<b>CCT:</b>	5000K (cool white) 4000K (neutral white)

All values typical unless otherwise stated (tolerance +/- 10%)

**WARNING: INSTALLATION & SECONDARY RETENTION:** The use of this product without proper installation and inspections, including secondary safety retention/securing, could cause severe injury or death. Dialight recommends that all installations should use secondary retention (appropriate to the installation environment) where applicable. It is the exclusive responsibility of the contractor, installer and/or end customer to: (a) determine the suitability of the product for its intended application; and, (b) ensure that the product is installed safely (with secondary retention where appropriate) and in compliance with all applicable laws and regulations. To the extent permissible under the relevant law, Dialight disclaims all responsibility for personal injury and/or other damage resulting from any dislodgement or other dislocation of this product.

# Ordering Information

## Vigilant® LED High Bay - Corded Model



Standard Model with 3 Meter Cable & Hook Mount									
Part Number	Legacy Part Number	Lumens	Watts	lm/W	Voltage	CCT	CRI	Lens	Beam Distribution
HEE-7MC2-EDHW-NGN	HEEGMC4PNHNG	27,500	185	149	100-277 VAC, 120-250 VDC	5000K	80	Clear Glass	Medium
HEE-4MC2-EDHW-NGN	HEE2MC4PNHNG	27,200	185	147	100-277 VAC, 120-250 VDC	5000K	80	Clear Polycarbonate	Medium
HEE-LMC2-EDHW-NGN	HEELMC4PNHNG	27,000	185	146	100-277 VAC, 120-250 VDC	5000K	80	Diffused Domed Polycarbonate	Medium
HEE-7EC2-EDHW-NGN	HEEGEC4PNHNG	25,900	185	140	100-277 VAC, 120-250 VDC	5000K	80	Clear Glass	Oval
HEE-4EC2-EDHW-NGN	HEE2EC4PNHNG	25,600	185	138	100-277 VAC, 120-250 VDC	5000K	80	Clear Polycarbonate	Oval
HEE-LEC2-EDHW-NGN	HEELEC4PNHNG	25,300	185	137	100-277 VAC, 120-250 VDC	5000K	80	Diffused Domed Polycarbonate	Oval
HEE-7MC2-CDHW-NGN	HEEGMC4KNHNG	19,800	130	152	100-277 VAC, 120-250 VDC	5000K	80	Clear Glass	Medium
HEE-4MC2-CDHW-NGN	HEE2MC4KNHNG	19,600	130	151	100-277 VAC, 120-250 VDC	5000K	80	Clear Polycarbonate	Medium
HEE-LMC2-CDHW-NGN	HEELMC4KNHNG	19,400	130	149	100-277 VAC, 120-250 VDC	5000K	80	Diffused Domed Polycarbonate	Medium
HEE-7EC2-CDHW-NGN	HEEGEC4KNHNG	18,600	130	143	100-277 VAC, 120-250 VDC	5000K	80	Clear Glass	Oval
HEE-4EC2-CDHW-NGN	HEE2EC4KNHNG	18,400	130	142	100-277 VAC, 120-250 VDC	5000K	80	Clear Polycarbonate	Oval
HEE-LEC2-CDHW-NGN	HEELEC4KNHNG	18,200	130	140	100-277 VAC, 120-250 VDC	5000K	80	Diffused Domed Polycarbonate	Oval
HEE-7MC2-BDHW-NGN	HEEGMC4GNHNG	14,900	100	149	100-277 VAC, 120-250 VDC	5000K	80	Clear Glass	Medium
HEE-4MC2-BDHW-NGN	HEE2MC4GNHNG	14,800	100	148	100-277 VAC, 120-250 VDC	5000K	80	Clear Polycarbonate	Medium
HEE-LMC2-BDHW-NGN	HEELMC4GNHNG	14,600	100	146	100-277 VAC, 120-250 VDC	5000K	80	Diffused Domed Polycarbonate	Medium
HEE-7EC2-BDHW-NGN	HEEGEC4GNHNG	14,000	100	140	100-277 VAC, 120-250 VDC	5000K	80	Clear Glass	Oval
HEE-4EC2-BDHW-NGN	HEE2EC4GNHNG	13,900	100	139	100-277 VAC, 120-250 VDC	5000K	80	Clear Polycarbonate	Oval
HEE-LEC2-BDHW-NGN	HEELEC4GNHNG	13,700	100	137	100-277 VAC, 120-250 VDC	5000K	80	Diffused Domed Polycarbonate	Oval
HEE-7MC2-ADHW-NGN	HEEGMC4DNHNG	11,600	80	145	100-277 VAC, 120-250 VDC	5000K	80	Clear Glass	Medium
HEE-4MC2-ADHW-NGN	HEE2MC4DNHNG	11,500	80	144	100-277 VAC, 120-250 VDC	5000K	80	Clear Polycarbonate	Medium
HEE-LMC2-ADHW-NGN	HEELMC4DNHNG	11,400	80	143	100-277 VAC, 120-250 VDC	5000K	80	Diffused Domed Polycarbonate	Medium
HEE-7EC2-ADHW-NGN	HEEGEC4DNHNG	10,900	80	136	100-277 VAC, 120-250 VDC	5000K	80	Clear Glass	Oval
HEE-4EC2-ADHW-NGN	HEE2EC4DNHNG	10,800	80	135	100-277 VAC, 120-250 VDC	5000K	80	Clear Polycarbonate	Oval
HEE-LEC2-ADHW-NGN	HEELEC4DNHNG	10,700	80	134	100-277 VAC, 120-250 VDC	5000K	80	Diffused Domed Polycarbonate	Oval

### Notes

Note 1: Models in chart above are 5000K CCT. For 4000K CCT change the 6th character from C to N & deduct 3% from the lumen table.

Note 2: Flat clear acrylic lens available, consult local Dialight sales office for availability.

**DISCLAIMER:** All information provided is, to the best of Dialight's knowledge, accurate as of the date of publication, but is subject to change without notice and does not form part of any contract with Dialight. When ordering please refer to [www.dialight.com](http://www.dialight.com) for current versions of: (a) relevant product documentation (including the most up to date product data sheets); (b) Dialight terms and conditions of sale; and, (c) the relevant product warranty. All information provided is, to Dialight's knowledge, accurate at the date of publication, but is subject to change without notice and does not form part of any contract with Dialight. In the event of any discrepancy between this document and information provided on our website, the latter shall prevail.

# Ordering Information

## Vigilant® LED High Bay - Integrated Wiring Box Model



Integrated Wiring Box - Standard with HBXW3 Bracket									
Part Number	Legacy Part Number	Lumens	Watts	lm/W	Voltage	CCT	CRI	Lens	Beam Distribution
HWE-7MC2-EDAN-NGN	HEEGMC4PNJNG	27,500	185	149	100-277 VAC, 120-250 VDC	5000K	80	Clear Glass	Medium
HWE-4MC2-EDAN-NGN	HEE2MC4PNJNG	27,200	185	147	100-277 VAC, 120-250 VDC	5000K	80	Clear Polycarbonate	Medium
HWE-LMC2-EDAN-NGN	HEELMC4PNJNG	27,000	185	146	100-277 VAC, 120-250 VDC	5000K	80	Diffused Domed Polycarbonate	Medium
HWE-7EC2-EDAN-NGN	HEEGEC4PNJNG	25,900	185	140	100-277 VAC, 120-250 VDC	5000K	80	Clear Glass	Oval
HWE-4EC2-EDAN-NGN	HEE2EC4PNJNG	25,600	185	138	100-277 VAC, 120-250 VDC	5000K	80	Clear Polycarbonate	Oval
HWE-LEC2-EDAN-NGN	HEELEC4PNJNG	25,300	185	137	100-277 VAC, 120-250 VDC	5000K	80	Diffused Domed Polycarbonate	Oval
HWE-7MC2-CDAN-NGN	HEEGMC4KNJNG	19,800	130	152	100-277 VAC, 120-250 VDC	5000K	80	Clear Glass	Medium
HWE-4MC2-CDAN-NGN	HEE2MC4KNJNG	19,600	130	151	100-277 VAC, 120-250 VDC	5000K	80	Clear Polycarbonate	Medium
HWE-LMC2-CDAN-NGN	HEELMC4KNJNG	19,400	130	149	100-277 VAC, 120-250 VDC	5000K	80	Diffused Domed Polycarbonate	Medium
HWE-7EC2-CDAN-NGN	HEEGEC4KNJNG	18,600	130	143	100-277 VAC, 120-250 VDC	5000K	80	Clear Glass	Oval
HWE-4EC2-CDAN-NGN	HEE2EC4KNJNG	18,400	130	142	100-277 VAC, 120-250 VDC	5000K	80	Clear Polycarbonate	Oval
HWE-LEC2-CDAN-NGN	HEELEC4KNJNG	18,200	130	140	100-277 VAC, 120-250 VDC	5000K	80	Diffused Domed Polycarbonate	Oval
HWE-7MC2-BDAN-NGN	HEEGMC4GNJNG	14,900	100	149	100-277 VAC, 120-250 VDC	5000K	80	Clear Glass	Medium
HWE-4MC2-BDAN-NGN	HEE2MC4GNJNG	14,800	100	148	100-277 VAC, 120-250 VDC	5000K	80	Clear Polycarbonate	Medium
HWE-LMC2-BDAN-NGN	HEELMC4GNJNG	14,600	100	146	100-277 VAC, 120-250 VDC	5000K	80	Diffused Domed Polycarbonate	Medium
HWE-7EC2-BDAN-NGN	HEEGEC4GNJNG	14,000	100	140	100-277 VAC, 120-250 VDC	5000K	80	Clear Glass	Oval
HWE-4EC2-BDAN-NGN	HEE2EC4GNJNG	13,900	100	139	100-277 VAC, 120-250 VDC	5000K	80	Clear Polycarbonate	Oval
HWE-LEC2-BDAN-NGN	HEELEC4GNJNG	13,700	100	137	100-277 VAC, 120-250 VDC	5000K	80	Diffused Domed Polycarbonate	Oval
HWE-7MC2-ADAN-NGN	HEEGMC4DNJNG	11,600	80	145	100-277 VAC, 120-250 VDC	5000K	80	Clear Glass	Medium
HWE-4MC2-ADAN-NGN	HEE2MC4DNJNG	11,500	80	144	100-277 VAC, 120-250 VDC	5000K	80	Clear Polycarbonate	Medium
HWE-LMC2-ADAN-NGN	HEELMC4DNJNG	11,400	80	143	100-277 VAC, 120-250 VDC	5000K	80	Diffused Domed Polycarbonate	Medium
HWE-7EC2-ADAN-NGN	HEEGEC4DNJNG	10,900	80	136	100-277 VAC, 120-250 VDC	5000K	80	Clear Glass	Oval
HWE-4EC2-ADAN-NGN	HEE2EC4DNJNG	10,800	80	135	100-277 VAC, 120-250 VDC	5000K	80	Clear Polycarbonate	Oval
HWE-LEC2-ADAN-NGN	HEELEC4DNJNG	10,700	80	134	100-277 VAC, 120-250 VDC	5000K	80	Diffused Domed Polycarbonate	Oval

### Notes

Note 1: Models in chart above are 5000K CCT. For 4000K CCT change the 6th character from C to N & deduct 3% from the lumen table.

Note 2: Flat clear acrylic lens available. Consult local Dialight sales office for availability.

Note 3: Occupancy sensor options available. Consult local Dialight sales office for availability.

**DISCLAIMER:** All information provided is, to the best of Dialight's knowledge, accurate as of the date of publication, but is subject to change without notice and does not form part of any contract with Dialight. When ordering please refer to [www.dialight.com](http://www.dialight.com) for current versions of: (a) relevant product documentation (including the most up to date product data sheets); (b) Dialight terms and conditions of sale; and, (c) the relevant product warranty. All information provided is, to Dialight's knowledge, accurate at the date of publication, but is subject to change without notice and does not form part of any contract with Dialight. In the event of any discrepancy between this document and information provided on our website, the latter shall prevail.

# Ordering Information

## Vigilant® LED High Bay - Battery Backup Model



Battery Backup Model - 20W								
Part Number	Lumens	Watts	lm/W	Voltage	CCT	CRI	Lens	Beam Distribution
HEE-7MCG-EDHN-NGH	27,500	191	144	230/240 VAC	5000K	80	Glass - Clear	Medium
HEE-4MCG-EDHN-NGH	27,200	191	142	230/240 VAC	5000K	80	Clear Polycarbonate	Medium
HEE-7MCG-CDHN-NGH	19,800	136	146	230/240 VAC	5000K	80	Glass - Clear	Medium
HEE-4MCG-CDHN-NGH	19,600	136	144	230/240 VAC	5000K	80	Clear Polycarbonate	Medium
HEE-7MCG-BDHN-NGH	14,900	106	141	230/240 VAC	5000K	80	Glass - Clear	Medium
HEE-4MCG-BDHN-NGH	14,800	106	140	230/240 VAC	5000K	80	Clear Polycarbonate	Medium
HEE-7MCG-ADHN-NGH	11,600	86	135	230/240 VAC	5000K	80	Glass - Clear	Medium
HEE-4MCG-ADHN-NGH	11,500	86	134	230/240 VAC	5000K	80	Clear Polycarbonate	Medium

All values typical unless otherwise stated (tolerance +/- 10%)

*DISCLAIMER: All information provided is, to the best of Dialight's knowledge, accurate as of the date of publication, but is subject to change without notice and does not form part of any contract with Dialight. When ordering please refer to [www.dialight.com](http://www.dialight.com) for current versions of: (a) relevant product documentation (including the most up to date product data sheets); (b) Dialight terms and conditions of sale; and, (c) the relevant product warranty. All information provided is, to Dialight's knowledge, accurate at the date of publication, but is subject to change without notice and does not form part of any contract with Dialight. In the event of any discrepancy between this document and information provided on our website, the latter shall prevail.*

## Vigilant® LED Low Bay - CE Corded Model & Integrated Wiring Box Model



### Corded Model



**Mechanical Information:**

**Fixture weight:**  
8.2 kg (18 lbs)

**Shipping weight:**  
10.9 kg (24 lbs)

**Mounting:**  
Stainless Steel Hook

**Power Cord:**  
3 meters, H07RN-F Heavy Duty

**Prefix:** LEE

### Integrated Wiring Box



**Mechanical Information:**

**Fixture weight:**  
9.1 kg (20 lbs)

**Shipping weight:**  
11.8 kg (26 lbs)

**Mounting:**  
Various Kits (see page 15)

**Wiring Box Cable Entries:**  
M25 x 3

**Terminals:**  
4mm<sup>2</sup> x 5

**Prefix:** LWE

Comparison		
	Warranty	L70
Dialight LED High Bay	10yr	>150,000
Metal Halide	1	15,000
High Pressure Sodium	1	20,000

**Certifications & Ratings:**

EN 60598:2015	IP66 to EN 60529
EN 60598-2-1 (ed.1), IEC 60598-2-1 (ed.8)	IK10 to EN 50102 (Polycarbonate lens)
EN 60598-2-24:2013	IK06 to EN 50102 (Acrylic lens)
EN 62471:2008, EN 62778:2014	IK05 to EN 50102 (Glass lens)
EN 62493:2010	D-Marking to EN 60598 2-2
IEC60068	ENEC
Salt spray testing - severity 1	L70 >150,00 hours @ 25°C ambient

**Variable Dimming as Standard:**

**Variable Dimming Control:** 0-10 VDC

**Dimming Range:** 10 VDC = 100% light output  
0 VDC = <5% light output

**Electrical Specifications:**

**Operating Voltage:** 100-277 VAC, 50/60 Hz  
120-250 VDC

**Total system power consumption:** See table

**Operating Temp:** -40°C to +65°C

**Harmonics:** IEC 61000-3-2

**Noise requirement /EMC:** EN 61547: 2009  
Radiated and Conducted Emissions: EN 55015

**EMC Immunity:** EN 61547: 2009

**Transient protection:** 100-277 VAC models tested to withstand up to 8kV/4kA per IEEE C62.41. 347-480 VAC models tested to withstand up to 6kV/3kA per IEEE C62.41

**THD:** < 20%

**Power Factor:** > 0.9

**Power Supply:**

**ALT: (accelerated life testing)** Over 15 yr equivalent at 24/7 service

**MTBF: (mean time between failures)** Over 300 years with annual failure rate less than 0.3% expected

**Driver:** Fully potted and sealed for superior protection

**Construction:**

**Housing:** Copper-free aluminium

**Finish:** Superior dual coat finish  
-Sealed polyester topcoat  
-Chemical-resistant epoxy primer

**Lens:** See table

**Gaskets:** Silicone free

**Screws:** Stainless steel 316

**Vibration:** Up to 5G @ 10-150Hz for 750,000 cycles, per IEC 60068-2-6 for luminaire only

**Shock:** 50G half-sine for 3 cycles, per IEC 60068-2-27 for luminaire only

**Photometric Information:**

**CRI:** 80

**CCT:** 5000K (cool white)  
4000K (neutral white)

All values typical unless otherwise stated (tolerance +/- 10%)

**WARNING: INSTALLATION & SECONDARY RETENTION:** The use of this product without proper installation and inspections, including secondary safety retention/securing, could cause severe injury or death. Dialight recommends that all installations should use secondary retention (appropriate to the installation environment) where applicable. It is the exclusive responsibility of the contractor, installer and/or end customer to: (a) determine the suitability of the product for its intended application; and, (b) ensure that the product is installed safely (with secondary retention where appropriate) and in compliance with all applicable laws and regulations. To the extent permissible under the relevant law, Dialight disclaims all responsibility for personal injury and/or other damage resulting from any dislodgement or other dislocation of this product.

## Vigilant® LED Low Bay - CE Battery Backup Model





### Mechanical Information:

**Fixture weight:**  
39 lbs (17.7 kg) max

**Shipping weight:**  
46 lbs (20.9 kg) max

**Mounting:**  
Stainless Steel Hook

Prefix: LEE



Dimensions in mm (inches)

### Certifications & Ratings:

10 year warranty (excluding battery)	IK10 to EN 50102 (Polycarbonate lens)
EN 60598-1:2015, IEC 60598-1:2014	IK06 to EN 50102 (Acrylic lens)
EN 60598-2-1:1989, IEC 60598-2-1:2020	IK05 to EN 50102 (Glass lens)
IEC60068	D-Marking to EN 60598 2-24
Salt spray testing - severity 1	L70 >150,000 hours @ 25°C ambient
IP66 to EN 60529	

### Variable Dimming as Standard:

**Variable Dimming Control:** 0-10 VDC

**Dimming Range:** 10 VDC = 100% light output  
0 VDC = <10% light output

### Electrical Specifications:

**Operating Voltage:** 230/240 VAC

**Total system power consumption:** See table

**Operating Temp:** -20°C to +55°C

**Harmonics:** IEC 61000-3-2

**Noise requirement /EMC:** EN 61547: 2009  
Radiated and Conducted  
Emissions: EN 55015

**EMC Immunity:** EN 61547: 2009

**Transient protection:** 120-277 VAC models tested to  
withstand up to 6kV/3kA per IEEE  
C62.41.

**THD:** < 20%

**Power Factor:** > 0.9

### Construction:

**Housing:** Copper-free aluminium

**Finish:** Superior dual coat finish  
-Sealed polyester topcoat  
-Chemical-resistant epoxy primer

**Lens:** See table

**Screws:** Stainless steel 316

### Photometric Information:

**CRI:** 80

**CCT:** 5000K (cool white)  
4000K (neutral white)

All values typical unless otherwise stated (tolerance +/- 10%)

**WARNING: INSTALLATION & SECONDARY RETENTION:** The use of this product without proper installation and inspections, including secondary safety retention/securing, could cause severe injury or death. Dialight recommends that all installations should use secondary retention (appropriate to the installation environment) where applicable. It is the exclusive responsibility of the contractor, installer and/or end customer to: (a) determine the suitability of the product for its intended application; and, (b) ensure that the product is installed safely (with secondary retention where appropriate) and in compliance with all applicable laws and regulations. To the extent permissible under the relevant law, Dialight disclaims all responsibility for personal injury and/or other damage resulting from any dislodgement or other dislocation of this product.



# Ordering Information

## Vigilant® LED Low Bay - All Models



Part Number	Legacy Part Number	Lumens	Watts	lm/W	Voltage	CCT	CRI	Lens	Beam Distribution
<b>Standard Models with 3m Cable &amp; Hook Mount</b>									
LEELUC2CDHWNGN		17,200	150	115	100-277 VAC, 120-250 VDC	5000K	80	Diffused Domed Polycarbonate	Ultra Wide
LEELUC2BDHWNGN		13,100	112	117	100-277 VAC, 120-250 VDC	5000K	80	Diffused Domed Polycarbonate	Ultra Wide
LEELUC29DHWNGN		9,200	78	118	100-277 VAC, 120-250 VDC	5000K	80	Diffused Domed Polycarbonate	Ultra Wide
LEELUC26DHWNGN	LBW1C1DEUH	6,400	50	128	100-277 VAC, 120-250 VDC	5000K	80	Diffused Domed Polycarbonate	Ultra Wide
LEELUC24DHWNGN	LBW1C5AEUH	3,900	38	103	100-277 VAC, 120-250 VDC	5000K	80	Diffused Domed Polycarbonate	Ultra Wide
<b>Integrated Wiring Box - comes standard with bracket HBXW3</b>									
LWELUC2CDANNGN		17,200	150	115	100-277 VAC, 120-250 VDC	5000K	80	Diffused Domed Polycarbonate	Ultra Wide
LWELUC2BDANNGN		13,100	112	117	100-277 VAC, 120-250 VDC	5000K	80	Diffused Domed Polycarbonate	Ultra Wide
LWELUC29DANNGN		9,200	78	118	100-277 VAC, 120-250 VDC	5000K	80	Diffused Domed Polycarbonate	Ultra Wide
LWELUC26DANNGN		6,400	50	128	100-277 VAC, 120-250 VDC	5000K	80	Diffused Domed Polycarbonate	Ultra Wide
LWELUC24DANNGN		3,900	38	103	100-277 VAC, 120-250 VDC	5000K	80	Diffused Domed Polycarbonate	Ultra Wide
<b>Battery Backup - 10W</b>									
LEE-LUCG-9DHN-NGG		9,200	84	110	230/240 VAC	5000K	80	Polycarbonate Dome - Diffused	Ultra Wide
LEE-LUCG-6DHN-NGG		6,400	56	114	230/240 VAC	5000K	80	Polycarbonate Dome - Diffused	Ultra Wide

**Notes**


Note 1: Models in chart above are 5000K CCT. For 4000K CCT change the 6th character from C to N & deduct 3% from the lumen table.

Note 2: Models with integrated wiring box are upgradeable to DALI & Wireless controls. Consult local Dialight sales office for availability.


**WARNING: INSTALLATION & SECONDARY RETENTION:** The use of this product without proper installation and inspections, including secondary safety retention/securing, could cause severe injury or death. Dialight recommends that all installations should use secondary retention (appropriate to the installation environment) where applicable. It is the exclusive responsibility of the contractor, installer and/or end customer to: (a) determine the suitability of the product for its intended application; and, (b) ensure that the product is installed safely (with secondary retention where appropriate) and in compliance with all applicable laws and regulations. To the extent permissible under the relevant law, Dialight disclaims all responsibility for personal injury and/or other damage resulting from any dislodgement or other dislocation of this product.

# Dimensional Drawings - High Bay


## Corded Model with Hook Mount



## Integrated Wiring Box




## Battery Backup




**DISCLAIMER:** All information provided is, to the best of Dialight's knowledge, accurate as of the date of publication, but is subject to change without notice and does not form part of any contract with Dialight. When ordering please refer to [www.dialight.com](http://www.dialight.com) for current versions of: (a) relevant product documentation (including the most up to date product data sheets); (b) Dialight terms and conditions of sale; and, (c) the relevant product warranty. All information provided is, to Dialight's knowledge, accurate at the date of publication, but is subject to change without notice and does not form part of any contract with Dialight. In the event of any discrepancy between this document and information provided on our website, the latter shall prevail.

# Dimensional Drawings - Low Bay


## Corded Model with Hook Mount



## Integrated Wiring Box




## Battery Backup



**DISCLAIMER:** All information provided is, to the best of Dialight's knowledge, accurate as of the date of publication, but is subject to change without notice and does not form part of any contract with Dialight. When ordering please refer to [www.dialight.com](http://www.dialight.com) for current versions of: (a) relevant product documentation (including the most up to date product data sheets); (b) Dialight terms and conditions of sale; and, (c) the relevant product warranty. All information provided is, to Dialight's knowledge, accurate at the date of publication, but is subject to change without notice and does not form part of any contract with Dialight. In the event of any discrepancy between this document and information provided on our website, the latter shall prevail.


# Beam Distributions

## Medium




Maximum Candela = 12129.5 Located At Horizontal Angle = 0, Vertical Angle = 27.5  
 # 1 - Vertical Plane Through Horizontal Angles (0 - 180)  
 # 2 - Vertical Plane Through Horizontal Angles (90 - 270)

## Oval



Maximum Candela = 20128.4 Located At Horizontal Angle = 85, Vertical Angle = 2.5  
 # 1 - Vertical Plane Through Horizontal Angles (0 - 180)  
 # 2 - Vertical Plane Through Horizontal Angles (90 - 270)

## Ultra Wide




Maximum Candela = 789.7 Located At Horizontal Angle = 0, Vertical Angle = 57.5  
 # 1 - Vertical Plane Through Horizontal Angles (0 - 180)  
 # 2 - Vertical Plane Through Horizontal Angles (90 - 270)



**DISCLAIMER:** All information provided is, to the best of Dialight's knowledge, accurate as of the date of publication, but is subject to change without notice and does not form part of any contract with Dialight. When ordering please refer to [www.dialight.com](http://www.dialight.com) for current versions of: (a) relevant product documentation (including the most up to date product data sheets); (b) Dialight terms and conditions of sale; and, (c) the relevant product warranty. All information provided is, to Dialight's knowledge, accurate at the date of publication, but is subject to change without notice and does not form part of any contract with Dialight. In the event of any discrepancy between this document and information provided on our website, the latter shall prevail.

## Thermal Roll-Off



## Inrush Currents

### High Bay Models

HE Models	Watt	In rush current @ input voltage			Time duration of in rush current @ input voltage		
		120 VAC	230 VAC	277 VAC	120 VAC	230 VAC	277 VAC
26K	186	7.7A	14.8A	17.8A	2ms	2ms	2ms
19K	129	7.7A	14.8A	17.8A	2ms	2ms	2ms
14K	102	7.7A	14.8A	17.8A	2ms	2ms	2ms
11K	81	7.7A	14.8A	17.8A	2ms	2ms	2ms

### Low Bay Models

LE Models	Watt	In rush current @ input voltage			Time duration of in rush current @ input voltage		
		120 VAC	230 VAC	277 VAC	120 VAC	230 VAC	277 VAC
18K	154W	7.7A	14.8A	17.8A	2ms	2ms	2ms
14K	114W	7.7A	14.8A	17.8A	2ms	2ms	2ms
9K	80W	7.7A	14.8A	17.8A	2ms	2ms	2ms
6K	56W	7.7A	14.8A	17.8A	2ms	2ms	2ms
4K	42W	7.7A	14.8A	17.8A	2ms	2ms	2ms

DISCLAIMER: All information provided is, to the best of Dialight's knowledge, accurate as of the date of publication, but is subject to change without notice and does not form part of any contract with Dialight. When ordering please refer to [www.dialight.com](http://www.dialight.com) for current versions of: (a) relevant product documentation (including the most up to date product data sheets); (b) Dialight terms and conditions of sale; and, (c) the relevant product warranty. All information provided is, to Dialight's knowledge, accurate at the date of publication, but is subject to change without notice and does not form part of any contract with Dialight. In the event of any discrepancy between this document and information provided on our website, the latter shall prevail.

## Circuit Breaker

Model	Maximum # of Lights per Breaker @ 100 VAC			Maximum # of Lights per Breaker @ 120 VAC			Maximum # of Lights per Breaker @ 230 VAC			Maximum # of Lights per Breaker @ 277 VAC		
	C10	B16	C16	C10	B16	C16	C10	B16	C16	C10	B16	C16
11k	8	13	13	10	16	16	19	30	30	22	35	35
14k	6	10	10	8	12	12	15	24	24	17	28	28
19k	5	8	8	6	9	9	11	18	18	13	20	20
26k	3	5	5	4	7	7	8	13	13	9	15	15

## Lumen Maintenance Factor

% Lumen Output (120V)									
Ambient Temp (°C)	Hours								
	0	15000	30000	45000	60000	75000	90000	100000	150000
25	100%	98%	96%	95%	94%	92%	91%	90%	86%
30	99%	97%	95%	94%	93%	91%	90%	89%	85%
35	98%	96%	94%	93%	92%	91%	89%	89%	84%
40	97%	95%	94%	92%	91%	90%	88%	88%	84%
45	96%	94%	93%	91%	90%	89%	88%	87%	83%
50	95%	93%	92%	91%	89%	88%	87%	86%	82%
55	94%	92%	91%	90%	88%	87%	86%	85%	81%
60	94%	91%	90%	89%	88%	86%	85%	84%	81%
65	90%	88%	86%	84%	83%	81%	80%	79%	74%

## Battery Backup (BB) Lumen Output:

$$\text{BB Lumens} = (\text{BB Wattage}) \times (\text{Fixture Lumens} / \text{Fixture Wattage})$$

High Bay Example: HEE-7MCG-EDHN-NGH

$$\text{BB Lumens} = 20W \times (27,500 / 191)$$

$$\text{BB Lumens} = 2,880 \text{ lumens}$$

DISCLAIMER: All information provided is, to the best of Dialight's knowledge, accurate as of the date of publication, but is subject to change without notice and does not form part of any contract with Dialight. When ordering please refer to [www.dialight.com](http://www.dialight.com) for current versions of: (a) relevant product documentation (including the most up to date product data sheets); (b) Dialight terms and conditions of sale; and, (c) the relevant product warranty. All information provided is, to Dialight's knowledge, accurate at the date of publication, but is subject to change without notice and does not form part of any contract with Dialight. In the event of any discrepancy between this document and information provided on our website, the latter shall prevail.


## Accessories



- HBXW3-SSL-316M**
- 316 stainless steel bracket
- HBXW3-SSL-304M**
- 304 stainless steel bracket



- HBXCAB48**
- 48" long stainless steel safety rope (for use with safety bracket)
  - Includes 2 cables




- HBXSBDK**
- Sand blast kit (dome lens)
- HBXSBDL**
- Sacrificial dome lens



- HBXW3-SSL-304FTM**
- 304 stainless steel forward throw bracket
- HBXW3-SSL-316FTM**
- 316 stainless steel forward throw bracket



- HBXSB Safety Tabs**
- 316 stainless steel
  - Includes 4 tabs



- HBXSBK**
- Sand blast kit (flat lens)
- HBXSBL**
- Sacrificial flat lens




- HBXW3**
- Powder-coated aluminium swivel bracket




- HBBATTKIT20**
- 20W replacement battery
- HBBATTKIT10**
- 10W replacement battery




- HBXFSIRREMOTE**
- Remote for occupancy sensor



- HBXW3EUHOOK**
- Swivel bracket with hanging hook




- HBXOCC100277E**
- Field installable occupancy sensor for models prefixed with HWE or HCE



- HBXCBOCCFSPG**
- Sensor counterbalance
- HBXCBOCCFSPK**
- Powder coated steel
  - Sensor counterbalance
  - 316 stainless steel

HBXW3 - Swivel Bracket



*Wedge, accurate as of the date of publication, but is subject to change without notice and does not form part of any contract with Dialight. When ordering please refer to [www.dialight.com](http://www.dialight.com) for current versions of: (a) relevant product documentation (including the most up to date product data sheets); (b) Dialight terms and conditions of sale; and, (c) the relevant product warranty. All information provided is, to Dialight's knowledge, accurate at the date of publication, but is subject to change without notice and does not form part of any contract with Dialight. In the event of any discrepancy between this document and information provided on our website, the latter shall prevail.*

## Dialight Europe Ltd

60 Petty France, London,  
SW1H 9EU

Tel: +44 (0) 203 058 3540

sales-emea@dialight.com

## Middle East

Level 23 – Boulevard Plaza Tower 2

Emaar Boulevard, Dubai, U.A.E.

P.O. Box 124342

Tel: +971 (4) 409-6962

Fax: +971 (4) 409-6850

*DISCLAIMER: The use of this product without proper installation and inspections, including secondary safety retention/securing, could cause severe injury or death. Dialight products are intended for ultimate purchase, installation and operation by knowledgeable persons trained in the functional assessment, installation, use and maintenance of such products and all customers (including but not limited to end customers) are responsible for assessing the suitability of Dialight products for any given installation requirement. All values and performance data herein are design or typical values when measured under laboratory conditions. Whilst Dialight has used all reasonable endeavours to ensure the completeness and accuracy of information herein, this document does not form part of any contract with Dialight and Dialight does not assume any liability for damages resulting from use of this information or for any third party representations made in relation to Dialight products. The information herein is subject to change without notice. The products / software detailed herein are subject to applicable warranties and terms and conditions of use/purchase. Unless agreed otherwise in writing by an authorised representative of Dialight, Dialight does not represent that its products are fit for a particular purpose and accepts no liability for the installation and/or unauthorised use of its products. When ordering please refer to [www.dialight.com](http://www.dialight.com) for current versions of: (a) relevant product documentation (including the most up to date product data sheets); (b) Dialight terms and conditions of sale; and, (c) Dialight warranty terms. All information provided is, to Dialight's knowledge, accurate at the date of publication, but is subject to change without notice and does not form part of any contract with Dialight. In the event of any discrepancy between this document and information provided on our website, the latter shall prevail.*